

BOGE Typ DCZ	Leistung*		Abmessungen B/T/H mm	Anschluss	max. Druck bar	Gewicht kg
	m ³ /h	cfm				
4	8	4	214/210/ 390	G 1/4	16	2,9
5	15	8	214/210/ 565	G 1/4	16	4,4
6	25	13	214/210/ 815	G 1/4	16	6,0
8	35	21	214/210/1065	G 1/4	16	9,0
9	56	30	313/300/1160	G 3/8	16	23,0
11	72	40	313/300/1410	G 3/8	16	28,0
14	86	50	313/300/1610	G 1/2	15	33,0
25	145	85	265/280/1650	G 1	16	45
35	200	118	290/280/1680	G 1	16	54
45	255	150	340/340/1730	G 1	16	75
60	360	212	367/340/1750	G 1	16	92
70	400	235	395/420/1795	G 1 1/2	16	103
100	620	365	440/420/1800	G 1 1/2	16	134
125	750	441	485/420/1914	G 1 1/2	16	177
160	950	559	520/500/1950	G 2	16	209

© BOGE

Höhere Leistungen auf Anfrage

* m³/h bezogen auf 1 bar nach DIN ISO 7183

Behälter nach PED Einzelabnahme/CE-Norm