

Kompressor-Anlagen

BOGE Typ	Behälter- inhalt Liter	Hubvolumenstrom (Ansaugleistung)		Volumenstrom (Liefermenge nach VDMA 4362)		Kompressor- Drehzahl min ⁻¹	Zylinder- zahl	Motor		Maße B x T x H mm	Gewicht kg
		l/min	cfm	l/min	cfm			kW	PS		
10 bar / 150 psig Standard											
SB 270/ 150	150	270	9,5	185	6,5	650	1	1,5	2,0	1540x480x1030	160
SB 370/ 150	150	370	13,0	260	9,0	900	1	2,2	3,0	1540x480x1030	160
SB 475/ 150	150	475	17,0	340	12,0	1150	1	3,0	4,0	1640x570x1160	210
SB 710/ 350	350	710	25	542	20	730	2	4,0	5,0	1930x740x1470	305
SB 970/ 350	350	970	35	734	26	1010	2	5,5	7,5	1930x740x1470	325
SB 1330/ 500	500	1330	47	1009	36	920	3	7,5	10,0	1920x740x1530	380
SB 2030/ 750	750	2030	72	1508	54	1050	4	11,0	15,0	2000x750x1720	510
SB 2600/ 750	750	2600	92	1913	68	1350	4	15,0	20,0	2000x750x1720	520

Kompressor-Anlagen

BOGE Typ	Behälter- inhalt Liter	Hubvolumenstrom (Ansaugleistung)		Volumenstrom (Liefermenge nach VDMA 4362)		Kompressor- Drehzahl min ⁻¹	Zylinder- zahl	Motor		Maße B x T x H mm	Gewicht kg
		l/min	cfm	l/min	cfm			kW	PS		
15 bar / 220 psig Standard											
SBM 320/ 350	350	320	12	283	10	650	2	2,2	3,0	1720x700x1440	280
SBM 450/ 350	350	450	16	394	14	920	2	3,0	4,0	1720x700x1440	295
SBM 610/ 350	350	610	22	541	19	625	3	4,0	5,0	1930x740x1470	360
SBM 800/ 500	500	800	29	693	25	830	3	5,5	7,5	1920x740x1530	435
SBM 1100/ 500	500	1100	39	928	33	1130	3	7,5	10,0	1920x740x1530	445
SBM 1640/ 500	500	1640	58	1319	47	1130	4	11,0	15,0	2000x870x1720	575
SBM 2030/ 500	500	2030	72	1615	58	1400	4	15,0	20,0	2000x870x1720	525