

BOGE Typ	Höchst- druck**		Effektive Liefermenge*		Nennleistung				Abmessungen	Abmessungen	Druck- luft- aus- tritt	Gewicht	Gewicht
	bar	psig	m <sup>3</sup> /min	cfm	Haupt- antrieb kW	PS	Lüfter- motor kW	PS	schallgedämmt B x T x H (mm)	super- schallgedämmt B x T x H (mm)		schall- ged. kg	super- schallged. kg
SF 60-2	8	115	1,75-7,00	62- 247	45	60	1,1	1,5	1620x 960x1450	1620x 960x1950	G 1 <sup>1</sup> / <sub>4</sub>	885	915
	10	150	1,58-6,34	56- 224	45	60	1,1	1,5	1620x 960x1450	1620x 960x1950	G 1 <sup>1</sup> / <sub>4</sub>	885	915
	13	190	1,34-5,36	47- 189	45	60	1,1	1,5	1620x 960x1450	1620x 960x1950	G 1 <sup>1</sup> / <sub>4</sub>	885	915
SF 100-2	8	115	3,02-12,1	106- 428	75	100	2,2	3,0	2000x1065x1450	2000x1065x1950	G 1 <sup>1</sup> / <sub>2</sub>	1350	1400
	10	150	2,62-10,5	93- 371	75	100	2,2	3,0	2000x1065x1450	2000x1065x1950	G 1 <sup>1</sup> / <sub>2</sub>	1350	1400
	13	190	2,30- 9,2	81- 325	75	100	2,2	3,0	2000x1065x1450	2000x1065x1950	G 1 <sup>1</sup> / <sub>2</sub>	1350	1400
SF 150	8	115	4,60-18,4	163- 650	110	150	4,0	5,5	2365x1335x1750	2365x1335x2250	G 2 <sup>1</sup> / <sub>2</sub>	2200	2260
	10	150	4,08-16,3	144- 575	110	150	4,0	5,5	2365x1335x1750	2365x1335x2250	G 2 <sup>1</sup> / <sub>2</sub>	2200	2260
	13	190	3,55-14,2	125- 505	110	150	4,0	5,5	2365x1335x1750	2365x1335x2250	G 2 <sup>1</sup> / <sub>2</sub>	2200	2260

\*Liefermenge der Gesamtanlage nach ISO 1217, Anhang C, bei 20°C Umgebungstemperatur bei Höchstdruck.  
Emissions-Schalldruckpegel nach PN8NTC2.3 ab **71 dB(A)**.