

BOGE Typ	Höchstdruck		Effektive Liefermenge*		Motor- leistung		Abmessungen schalldämmt	Abmessungen superschallgedämmt / mit Radiallüfter	Druck- luft- aus- tritt	Gewicht schalldämmt / mit Radiallüfter	Gewicht super- schalldged. kg
	bar	psig	m³/min	cfm	kW	PS	B x T x H (mm)	B x T x H (mm)		kg	kg
SLF 30	8	115	1,06- 3,87	37-137	22	30	1830 x 966 x 1444	1830 x 966 x 1944	G 1¼	700/ 730	730
	10	150	1,06- 3,30	37-117	22	30	1830 x 966 x 1444	1830 x 966 x 1944	G 1¼	700/ 730	730
	13	190	1,06- 2,68	37- 95	22	30	1830 x 960 x 1444	1830 x 966 x 1944	G 1¼	700/ 730	730
SLF 40	8	115	1,06- 5,05	37-178	30	40	1830 x 966 x 1444	1830 x 966 x 1944	G 1¼	770/ 805	810
	10	150	1,06- 4,53	37-160	30	40	1830 x 966 x 1444	1830 x 966 x 1944	G 1¼	770/ 805	810
	13	190	1,06- 3,82	37-135	30	40	1830 x 966 x 1444	1830 x 966 x 1944	G 1¼	770/ 805	810
SLF 51	8	115	1,51- 6,71	53-237	37	50	2040 x 1090 x 1450	2040 x 1090 x 1950/2060	G 1¼	1020/1070	1070
	10	150	1,47- 6,04	52-213	37	50	2040 x 1090 x 1450	2040 x 1090 x 1950/2060	G 1¼	1020/1070	1070
	13	190	1,37- 4,98	48-176	37	50	2040 x 1090 x 1450	2040 x 1090 x 1950/2060	G 1¼	1020/1070	1070
SLF 61	8	115	1,55- 7,87	55-278	45	60	2040 x 1090 x 1450	2040 x 1090 x 1950/2060	G 1½	1150/1200	1200
	10	150	1,51- 6,92	53-244	45	60	2040 x 1090 x 1450	2040 x 1090 x 1950/2060	G 1½	1150/1200	1200
	13	190	1,42- 5,90	50-208	45	60	2040 x 1090 x 1450	2040 x 1090 x 1950/2060	G 1½	1150/1200	1200
SLF 75	8	115	1,55- 9,33	55-329	55	75	2040 x 1090 x 1450	2040 x 1090 x 1950/2060	G 1½	1270/1320	1320
	10	150	1,51- 8,40	53-297	55	75	2040 x 1090 x 1450	2040 x 1090 x 1950/2060	G 1½	1270/1320	1320
	13	190	1,46- 7,26	52-256	55	75	2040 x 1090 x 1450	2040 x 1090 x 1950/2060	G 1½	1270/1320	1320
SLF 101	8	115	4,22-13,64	149-482	75	100	2415 x 1335 x 1750	2415 x 1335 x 2250	G 2½	2200/ –	2260
	10	150	4,16-12,33	147-435	75	100	2415 x 1335 x 1750	2415 x 1335 x 2250	G 2½	2200/ –	2260
	13	190	4,00-10,58	141-374	75	100	2415 x 1335 x 1750	2415 x 1335 x 2250	G 2½	2200/ –	2260
SLF 125	8	115	4,22-15,70	149-554	90	125	2415 x 1335 x 1750	2415 x 1335 x 2250	G 2½	2250/ –	2310
	10	150	4,16-14,36	147-507	90	125	2415 x 1335 x 1750	2415 x 1335 x 2250	G 2½	2250/ –	2310
	13	190	4,00-12,56	141-443	90	125	2415 x 1335 x 1750	2415 x 1335 x 2250	G 2½	2250/ –	2310
SLF 221	8	115	6,46-28,21	228-996	160	220	3145 x 1910 x 2145	3145 x 1910 x 2645	DN 100	4500/ –	4600
	10	150	6,18-25,06	218-885	160	220	3145 x 1910 x 2145	3145 x 1910 x 2645	DN 100	4500/ –	4600
	13	190	5,46-20,36	193-719	160	220	3145 x 1910 x 2145	3145 x 1910 x 2645	DN 100	4500/ –	4600

BOGE Typ	Höchstdruck		Effektive Liefermenge*		Motor- leistung		Abmessungen schalldämmt	Abmessungen superschallgedämmt / mit Radiallüfter	Druck- luft- aus- tritt	Gewicht schalldämmt / mit Radiallüfter	Gewicht super- schalldged. kg
	bar	psig	m³/min	cfm	kW	PS	B x T x H (mm)	B x T x H (mm)		kg	kg
SLDF 30**	8	115	1,06-3,87	37-137	22	30	1830 x 966 x 1664	1830 x 966 x 1944	G 1¼	785/ –	815
	10	150	1,06-3,30	37-117	22	30	1830 x 966 x 1664	1830 x 966 x 1944	G 1¼	785/ –	815
	13	190	1,06-2,68	37- 95	22	30	1830 x 960 x 1664	1830 x 966 x 1944	G 1¼	785/ –	815
SLDF 40**	8	115	1,06-5,05	37-178	30	40	1830 x 966 x 1664	1830 x 966 x 1944	G 1¼	855/ –	895
	10	150	1,06-4,53	37-160	30	40	1830 x 966 x 1664	1830 x 966 x 1944	G 1¼	855/ –	895
	13	190	1,06-3,82	37-135	30	40	1830 x 966 x 1664	1830 x 966 x 1944	G 1¼	855/ –	895

*Liefermenge der Gesamtanlage nach ISO 1217, Anhang C, bei 20°C Umgebungstemperatur und Höchstdruck.

**mit Einschubtrockner

Emissions-Schalldruckpegel nach PN8NTC.2.3 ab **68 dB(A)**.